

## **Instructions for Users Running DB2**

This version does not include any DB2 drivers. If you are using a DB2 database you will need to install the DB2 drivers separately, and follow the below instructions to reference them. Please note that if you did this for a previous update of Templar it is not necessary to do it again. The DB2 drivers can be downloaded from IBM's website.

Also, you will need to set your database properties file to the db2.001 file.  
To set the database properties in Templar 5 you will need to:

- 1) Start Templar 5
- 2) Go to the Database Setup Tab of the Server Properties
- 3) Click on the Database Properties File dropdown menu and choose db2
- 4) Click Save on the Database Properties screen
- 5) Restart Templar 5.

If you are not comfortable performing any of these steps yourself please contact our Support Department and we would be glad to assist you.

## **How to set DB2 drivers for use with Templar 6**

### **Templar 6 Server on Windows Utilizing DB2 Database (Service):**

Define a new System Environment variable (it has to be a system one) – Click Properties on My Computer, then advanced properties and environment variables. Name the variable T5CLASSPATH and it should contain the path for the DB2 JDBC drivers. Such as: C:\DB2\jb2jcc.jar;c:\otherdirectory

### **Templar 6 Server on Unix Utilizing DB2 Database (start/stop script):**

You will need to change the following lines to the server startup scripts:

#### **Current classpath:**

```
CLASSPATH=".:patches.zip:iaik_jce.jar:T5.jar";export CLASSPATH
```

#### **Updated classpath:**

```
CLASSPATH=/Path_to_DB2_Drivers/db2java.zip:  
/Path_to_DB2_Drivers/jb2jcc.jar:patches.zip:iaik_jce.jar:T5.jar; export CLASSPATH
```