

Instructions for Users Running Informix

This update does not include any Informix drivers. If you are using an Informix database you will need to install the drivers separately, and follow the below instructions to reference them. Please note that if you did this for a previous update of Templar 6 it is not necessary to do it again.

Informix databases have a limitation to them that does not support derived tables. In order to accommodate the limitation, it is necessary to implement five stored procedures found in text format in the file `informix_stored_procedures.zip`.

Then you will need to set your Templar 6 to use the stored procedure by performing the following:

- 1) Start Templar 6
- 2) Go to the Database Setup Tab of the Server Properties
- 3) Click on the Database Properties File dropdown menu and choose informix
- 4) Click on the Edit Copy button under the Database Properties section
 - a. Change 'Table/Setting' to be TRADINGPARTNERAGREEMENT
Change 'Statement/Property' to be findByBothQualIDSQL
Change the value to be: {call GetTPA (?,?)}
 - b. Change 'Table/Setting' to be TRANSPORTDETAILS
Change 'Statement/Property' to be findAllActiveAS3Pull
Change the value to be: {call findAllActiveAS3Pull ()}
 - c. Change 'Table/Setting' to be TRANSPORTDETAILS
Change 'Statement/Property' to be findAS3ErrorMDNTPA
Change the value to be: {call findAS3ErrorMDNTPA()}
 - d. Change 'Table/Setting' to be TRANSPORTDETAILS
Change 'Statement/Property' to be findSMTPFlatFileTPA
Change the value to be: {call findSMTPFlatFileTPA (?,?)}
 - e. Change 'Table/Setting' to be TRANSPORTDETAILS
Change 'Statement/Property' to be findASFlatFileTPA
Change the value to be: {call findASFlatFileTPA (?)}
- 5) Click Save Copy (and then ok)
- 6) Click Save on the Database Properties screen
- 7) Restart Templar 6.

If you are not comfortable performing any of these steps yourself please contact our Support Department and we would be glad to assist you.

How to set Informix drivers for use with Templar 6

Templar 6 Server on Windows Utilizing Informix Database (Service):

Define a new System Environment variable (it has to be a system one) – Click Properties on My Computer, then advanced properties and environment variables. Name the variable T5CLASSPATH and it should contain the path for the Informix JDBC drivers. Such as:
C:\Informix\ifxjdbc.jar;c:\otherdirectory

Templar 6 Server on Unix Utilizing Informix Database (start/stop script):

You will need to modify the following line of the server startup script:

Current classpath:

```
CLASSPATH=".:patches.zip:iaik_jce.jar:T5.jar";export CLASSPATH
```

Updated classpath:

```
CLASSPATH=/Path_to_Informix_Drivers/ifxjdbc.jar:patches.zip:iaik_jce.jar:T5.jar; export CLASSPATH
```