

Instructions for Users Running Oracle

This update does not include any Oracle drivers. If you are using an Oracle database you will need to install the Oracle drivers separately, and follow the below instructions to reference them. Please note that if you did this for a previous update of Templar 6 it is not necessary to do it again. The Oracle drivers can be downloaded from Oracle's website.

Also, you will need to set your database properties file to the Oracle file.

To set the database properties in Templar 6 you will need to:

- 1) Start Templar 6
- 2) Go to the Database Setup Tab of the Server Properties
- 3) Click on the Database Properties File dropdown menu
 - a. If you are running Oracle 8 please choose "oracle"
 - b. If you are running Oracle 9 or 10 choose "oracle9"
- 4) Click Save on the Database Properties screen
- 5) Restart Templar 6.

If you are not comfortable performing any of these steps yourself please contact our Support Department and we would be glad to assist you.

How to set Oracle drivers for use with Templar 6

Templar 6 Server on Windows Utilizing Oracle Database (Service):

Define a new System Environment variable (it has to be a system one) – Click Properties on My Computer, then advanced properties and environment variables. Name the variable T5CLASSPATH and it should contain the path for the Oracle JDBC drivers. Such as: C:\Oracle\classes12.zip;c:\otherdirectory

Templar 6 Server on Unix Utilizing Oracle Database (start/stop script):

You will need to modify the following line of the server startup script:

Current classpath:

```
CLASSPATH=".:patches.zip:iaik_jce.jar:T5.jar";export CLASSPATH
```

Updated classpath:

```
CLASSPATH=/Path_to_Oracle_Drivers/classes12.zip:  
/Path_to_Oracle_Drivers/nls_charset12.zip:patches.zip:iaik_jce.jar:T5.jar; export  
CLASSPATH
```